

ASYS Group Technologies BCO 01 Basic Conveyor with one segment



Description

Basic edge belt conveyor system with a 530 mm long conveyor segment. The conveyor is used as a connecting element between 2 machines in a production line. The precise rail design allows quick and easy adjustment of the conveyor width using clamping levers. The powder coated steel frame ensures process stability and excellent durability.

Features

- _Anti-static conveyor belts
- _ SMEMA Interface
- _ Start / Stop push button

Options


- _ Inspection function 0/1
- _ Adjustable handover speed
- _ Electrical width adjustment
- _Transport height 850 mm \pm 50 mm
- _ Hinged dust cover 530 mm
- _ Hinged dust cover, with Interlock
- _ Rail extension
- _ Stopper cylinder
- _ Scanner mounting bracket with trigger, topside











BCO 01 Basic Conveyor with 1 segment

ASYS Handling Equipment - Basic Series

Basic Series

	BCO 01
Machine Configuration	
Transport height	950 mm ± 50 mm
Max. transport width	460 mm
Interface	SMEMA
Transfer direction	from left to right
Operating side	Front of the machine
Fixed rail	Front of the machine
Panel Dimensions	
Panel length	50 to 460 mm
Panel width	50 to 460 mm
Panel thickness	0.8 to 4.5 mm
Component clearance	± 40 mm
Panel weight	to 3 kg
Installation Requirements	
Power supply	230 V / 115 V, 50 / 60 Hz, ± 10%
Power supply system	L1 + N + PE
Power consumption	0,07 kW
Machine Description	
Length x Width x Height	530 x 797 x 953 mm
Color ^{a)}	Basic Light
Noise Level	< 75 dB
Upgrades	
Control panel T70	
Control function 0/99 ^{b)}	
Automatic width adjustment ^{b)}	
Good/Bad sorting	
Machine networking via IC Net	
Additional interface protocol	
a) RAL colors at a surcharge	

b) only with control panel T70

www.asys-group.com

ASTS Automatislerungssysteme G Benzstraße 10, D-89160 Dornstadt Germany Tel. (+49) 7348 9855 0 Fax (+49) 7348 9855 91 info@asys.de STS Group Asia Pte Ltd 0 Shaw Road #01-02/03 ingapore 367957 al. (+65) 6280 8887 ax (+65) 6858 5005 ales@asysgroup-asia.com

40 Satellite Boulevard NE Suite B1, Suwanee GA 30024 USA Fel. (+1) 770 246 9706 Fax (+1) 770 246 9866 Subject to change without notice.

all products. Technical specifications are subject to change without notice. Only features and technical data provided in purchasing contract are legally binding.