

ASYS Group Technologies BTT 01 Basic Turn Table



Description

The Basic Turn Table is typically located in a SMD line which requires a 90 degree turn or a sorting feature. The conveyor segment is mounted on an pneumatic turn table and PCBs are routed based upon the run mode or an external signal. Possible run modes are pass through, load, offload and sort. The powder coated steel frame ensures process stability and excellent durability.

Features


- _Turn
- _ Start / Stop push button
- _Anti-static conveyor belts
- _ SMEMA Interface

Options


- _ Transport height 850 mm ± 50 mm _ Electrical width adjustment

- _ Inlet conveyor 530 mm ^{c) d)} _ Outlet conveyor 530 mm ^{c) d)}









BTT 01 Basic Turn Table

ASYS Handling Equipment - Basic Series

Basic Series

| | BTT 01 |
|--|--------------------------------------|
| Machine Configuration | |
| Transport height | 950 mm ± 50 mm |
| Max. transport width | 460 mm |
| Interface | SMEMA |
| Transfer direction | from left to right |
| Operating side | Front of the machine |
| Fixed rail | Front of the machine |
| The adjacent upstream and downstream | modules must have screwed-on covers. |
| Panel Dimensions | |
| Panel length | 50 to 460 mm |
| Panel width | 50 to 460 mm |
| Panel thickness | 0.8 to 4.5 mm |
| Component clearance | ± 40 mm |
| Panel weight | to 3 kg |
| Installation Requirements | |
| Power supply | 230 V / 115 V, 50 / 60 Hz, ± 10% |
| Power supply system | L1 + N + PE |
| Power consumption | 0,16 kW |
| Air supply | 6 bar |
| Air consumption | 15 NI/min |
| Machine Description | |
| Length x Width x Height | 830 x 830 x 1060 mm |
| Color ^{a)} | Basic Light |
| Noise Level | < 75 dB |
| Upgrades | |
| Control panel T70 | |
| Additional interface protocol | |
| Automatic width adjustment ^{b)} | |
| Pass through with load, offload function | |
| Good/Bad sorting | |
| Machine networking via IC Net | |
| a) RAL colors at a surcharge | |
| b) only with control panel T70 | |

c) Connection of maximum 2 additional conveyors.

d) The conveyors must have screwed-on covers

www.asys-group.com

ASYS Automatisierungssysteme Gml Benzstraße 10, D-89160 Dornstadt Germany

Fax (+49) 7348 9855 9 info@asys.de KYS Group Asia Pte Ltd 10 Shaw Road #01-02/03 Singapore 367957 iel. (+65) 6280 8887 iax (+65) 6858 5005 ales@asysgroup-asia.com

40 Satellite Boulevard NE Suite B1, Suwanee SA 30024 USA fel. (+1) 770 246 9706 fax (+1) 770 246 9866 ubject to change without notice.

Some general descriptions and performance characteristics may not be applicable to all products. Technical specifications are subject to change without notice. Only features and technical data provided in purchasing contract are legally binding.

Printed in Germany